

NITROGEN ZINC BONNET REGULATORS



- Built-In Safety - A non-adjustable, precision, relief valve in every Taprite Regulator that cannot be removed or easily circumvented.
- Fail-Safe protection – In case of regulator failure the Integral Safety will instantly activate to protect system from overpressurization. Excess pressure is vented into atmosphere.
- Keg Security – Pressure in Keg can never exceed preset level of 55-60 psig prior to shutdown. After shutoff no additional pressure enters the system.
- Left-Hand Threads – High pressure ports (only) have left hand threads to prevent possible use as a low-pressure outlet.
- Non-removable Adjusting Screw with locknut - designed so if turned all the way in, pressure entering system stays at safe level.
- Nitrogen is widely used in the beer industry but also has been used for dispensing wine.



742HPN

Model Number	Description
742N	0-50 PSI, 60lb & 3000lb gauge, 5/16" barb shutoff with ball check black bonnet
742HPN	0-50 PSI, 60lb & 3000lb gauge, 5/16" barb shutoff with duck-bill check black bonnet
742HPN-100	0-50 PSI, 100lb & 3000lb gauge, 5/16" barb shutoff with duck-bill check black bonnet
5741PMHPNT	0-120 PSI, 160lb & 3000lb gauge, 5/16" barb shutoff with check valve black bonnet

