

PRIMARY REGULATORS 3000 SERIES



Taprite regulators have the highest flow rate in the industry. Robust design delivers performance, reliability and is unlikely to experience freeze up problems. Extremely durable and user friendly polycarbonate bonnets make adjustments a snap! Pull cap to adjust the pressure and push back to lock it in.

The TAPRITE ADVANTAGE

- High CO2 volumetric flow provides continuity in product dispensing
- Primary regulators connect directly to gas source
- Recommended operating pressure be limited to 2/3 of the gauge range for maximum accuracy
- UL approved per UL252 class IV rating for CO2
- Polycarbonate bonnet will not chip, break or fade
- 10 Micron filter built in to keep contaminants out of regulator
- One repair kit for primary and secondary
- Used primarily for Soda but can be used for other applications.



3741

Model Number	Description
3735	Primary Soda 1Px5P 160#, CO2 FTG, HRZ MFLD 5 x 1/4F-CV, 2000# SM BLACK BONNET
3741	Primary Soda 1P1P 160# CO2 FT, 1/4F CVOUT, 2000#SM BLACK BONNET
3752	Primary Soda 2Px2P 160#, CO2 FTG 1/4-CV OUT, 2000# SM BLACK BONNET
3753	Primary Soda 2P3P 160#, CO2 FTG, 3X 1/4F CV 2000# SM BLACK BONNET
3754	Primary Soda 2Px4P (2X2) 160#, CO2 FTG 1.4F CV OUT, 2000# SM BLACK BONNET
3756-01	Primary Soda 2Px6P (3X3) 100# C02 FTG 1/4F CV 2000# SM BLACK BONNET



3248 Northwestern Dr., San Antonio, Texas 78238 • 210-523-0800 • Fax 210-646-6009 • sales@taprite.com

taprite.com